

Technical specifications		MIX40se	MIX40sp 40 Litros	MIX40spv	MIX65se	MIX65sp 65 Litros	MIX65spv	MIX95se	MIX95sp 95 Litros	MIX95spv	MIX165sp 165 Litros	MIX165spv
Motores		1	2	2	1	2	2	1	2	2	2	2
Volumen artesa	Litros	40	40	40	65	65	65	95	95	95	165	165
Capacidad artesa												
Masa gruesa/seca	kg	± 4 to 16	± 4 to 16	± 4 to 16	± 6 to 27	± 6 to 27	± 6 to 27	± 13 to 43	± 13 to 43	± 13 to 43	± 18 to 80	± 18 to 80
Masa fina/húmeda	kg	± 4 to 24	± 4 to 24	± 4 to 24	± 6 to 40	± 6 to 40	± 6 to 40	± 13 to 65	± 13 to 65	± 13 to 65	± 18 to 120	± 18 to 120
Velocidad pala	rpm	47 (50Hz) 56 (60Hz)	47 (50Hz) 56 (60Hz)	20 - 90 (50/60Hz)	47 (50Hz) 56 (60Hz)	47 (50Hz) 56 (60Hz)	20 - 90 (50/60Hz)	47 (50Hz) 56 (60Hz)	47 (50Hz) 56 (60Hz)	20 - 90 (50/60Hz)	47 (50Hz) 56 (60Hz)	35 - 75 (50/60Hz)
Velocidad artesa	rpm	-	14 (50Hz) 16 (60Hz)	14 (50Hz) 16 (60Hz)	-	14 (50Hz) 16 (60Hz)	14 (50Hz) 16 (60Hz)	-	14 (50Hz) 16 (60Hz)	14 (50Hz) 16 (60Hz)	11 (60Hz)	9 (50Hz) 11 (60Hz)
Acabado			Acero inoxidable		Acero inoxidable			Acero inoxidable			Acero inoxidable	
Bancada			Aluminio alimentario		Aluminio alimentario			Aluminio alimentario			Aluminio alimentario	
Pala			POM alimentario		POM alimentario			POM alimentario			POM alimentario	
Artesa												
Potencia total	HP	0,25	0,58	0,58	0,33	0,66	0,66	0,75	1,08	1,08	2,5	2,5
	kW	0,18	0,43	0,43	0,25	0,5	0,5	0,55	0,8	0,8	1,87	1,87
Peso neto	kg	± 90	± 103	± 105	± 110	± 123	± 125	± 144	± 157	± 159	± 283	± 285
Peso bruto	kg	± 106	± 119	± 121	± 126	± 139	± 141	± 164	± 177	± 179	± 372	± 374

Dimensiones	MIX40s	MIX65s	MIX95s	MIX165s
Cm				
A	58	69	76	91
B	86	99	111	125
C	100	106	119	133
D	117	130	146	165
E	116	130	144	164
F	67	70	78	93
G	34	35	32	44
Embalaje	99x71x124	99x71x124	112x80x139	135x108x155
m ³	0,87	0,87	1,25	2,26

